

1: Identification

Product identifier

Product name: Aluminum etchant

Stock number: 44581

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar, A Johnson Matthey Company
Johnson Matthey Catalog Company, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com
www.alfa.com

Information Department:

Product Safety Department
Health, Safety and Environmental Department

Emergency telephone number:

Call Carechem 24 at +44 (0) 1865 407333

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2: Hazard(s) identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



C; Corrosive

R34: Causes burns.

Information concerning particular hazards for human and environment: Not applicable

Hazards not otherwise classified No information known.

Label elements

Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS05

Signal word

 Danger

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D2B - Toxic material causing other toxic effects

E - Corrosive material



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3

FIRE 1 Flammability = 1

REACTIVITY 2 Physical Hazard = 2

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3: Composition/information on ingredients

Chemical characterization: Substances

CAS# Description:

Aluminum etchant

4: First-aid measures

Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

Product name: Aluminum etchant

(Contd. of page 1)

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed

Causes severe skin burns.

Causes serious eye damage.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5: Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Product is not flammable. Use fire-fighting measures that suit the surrounding fire.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Phosphorus oxides

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards: No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7: Handling and storage

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires: The product is not flammable

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from strong bases.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Specific end use(s) No further relevant information available.

8: Exposure controls/personal protection

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Orthophosphoric acid

mg/m3

ACGIH TLV 1; 3-STEL

Belgium TWA 1; 3-STEL

Denmark TWA 1

Finland TWA 1; 3-STEL (skin)

France TWA 1; 3-STEL

Ireland TWA 2-STEL

Netherlands TWA 1; 2-STEL

Sweden TWA 1; 3-STEL

Switzerland TWA 1

United Kingdom TWA 2-STEL

OSHA PEL 1

Acetic acid

ppm

ACGIH TLV 10; 15-STEL

Australia TWA 10; 15-STEL

Austria MAK 10

Belgium 10; 15-STEL

Denmark TWA 10

Finland TWA 10; 15-STEL (skin)

France VLE 10

Germany MAK 10

(Contd. on page 3)

Product name: Aluminum etchant

(Contd. of page 2)

Hungary 4; 8-STEL
Japan OEL 10
Korea TLV 10; 15-STEL
Netherlands MAC-TGG 10
Norway TWA 10
Poland TWA 2; 14-STEL
Russia 2-STEL (skin)
Sweden NGV 5; 10-KTV
Switzerland MAK-W 10; 20-KZG-W
United Kingdom 10; 15-STEL
USA PEL 10

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Penetration time of glove material (in minutes) Not determined

Eye protection:

Tightly sealed goggles

Full face protection

Body protection: Protective work clothing.

9: Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid

Odor: Not determined

Odor threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: Not determined

Boiling point/Boiling range: 100 °C (212 °F)

Sublimation temperature / start: Not determined

Flash point: Not determined

Flammability (solid, gaseous) Not determined.

Ignition temperature: Not determined

Decomposition temperature: Not determined

Auto igniting: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined

Upper: Not determined

Vapor pressure: Not determined

Density at 20 °C (68 °F): 1.45 g/cm³ (12.1 lbs/gal)

Relative density Not determined.

Vapor density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

Water: Fully miscible

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic: Not determined.

kinematic: Not determined.

Other information No further relevant information available.

10: Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No further relevant information available.

Incompatible materials:

Oxidizing agents

Bases

Hazardous decomposition products:

Phosphorus oxides (e.g. P₂O₅)

Nitrogen oxides

Carbon monoxide and carbon dioxide

11: Toxicological information

Information on toxicological effects

Acute toxicity: Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: Causes severe skin burns.

Eye irritation or corrosion: Causes serious eye damage.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

(Contd. on page 4)
USA

Product name: Aluminum etchant

(Contd. of page 3)

Carcinogenicity: No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.
Reproductive toxicity: No effects known.
Specific target organ system toxicity - repeated exposure: No effects known.
Specific target organ system toxicity - single exposure: No effects known.
Aspiration hazard: No effects known.
Subacute to chronic toxicity:
 Phosphoric acid is corrosive and irritates skin, eyes and mucous membranes on contact. Severe burns are possible. Dilute solutions will have a reduced effect.
 Acetic acid is corrosive and causes burns, lachrymation and conjunctivitis. It may cause skin ulcers and dermatitis. Inhalation or ingestion may cause irritation.
 Severity of symptoms is a function of concentration.
Subacute to chronic toxicity: No effects known.
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.



12: Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.
Additional ecological information:
General notes:
 Do not allow material to be released to the environment without proper governmental permits.
 Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.
 Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.

13: Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14: Transport information

UN-Number	UN1760
DOT, IMDG, IATA	
UN proper shipping name	Corrosive liquids, n.o.s. (Aluminum etchant)
DOT	CORROSIVE LIQUID, N.O.S. (Aluminum etchant)
IMDG, IATA	
Transport hazard class(es)	
DOT	
	
Class	8 Corrosive substances.
Label	8
Class	8 (C9) Corrosive substances
Label	8
IMDG, IATA	
	
Class	8 Corrosive substances.
Label	8
Packing group	II
DOT, IMDG, IATA	
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Marine Pollutant (DOT):	No
UN "Model Regulation":	UN1760, Corrosive liquids, n.o.s. (Aluminum etchant), 8, II

15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
National regulations
 All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
 All components of this product are listed on the Canadian Domestic Substances List (DSL).
SARA Section 313 (specific toxic chemical listings) Substance is not listed.
California Proposition 65
Prop 65 - Chemicals known to cause cancer Substance is not listed.
Prop 65 - Developmental toxicity Substance is not listed.
Prop 65 - Developmental toxicity, female Substance is not listed.
Prop 65 - Developmental toxicity, male Substance is not listed.
Information about limitation of use:
 For use only by technically qualified individuals.
 This product is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

(Contd. on page 5)

Product name: Aluminum etchant

(Contd. of page 4)

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

REACH - Pre-registered substances Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16: Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)